

# LEARNING DESIGN RULES FOR WIND BRACINGS IN TALL BUILDINGS

**Tomasz Arciszewski<sup>1</sup>, Associate Member ASCE, Eric Bloedorn<sup>2</sup>  
Ryszard S. Michalski<sup>3</sup>, Mohamad Mustafa<sup>4</sup> and Janusz Wnek<sup>5</sup>**

## ABSTRACT

This paper describes a methodology for applying machine learning to problems of conceptual design, and presents a case study of learning design rules for wind bracings in tall buildings. Design rules are generated by induction from examples of minimum weight designs. This study investigates the applicability of machine learning methods which are capable of *constructive induction*, that is of automatically searching for and generating problem-relevant attributes beyond those originally provided. The decision rules generated by machine learning programs specify design configurations which are recommended, typical, infeasible, or those which are to be avoided. The learned rules captured some of the essential expert's understanding of the design characteristics involved in selecting wind bracings for tall buildings. These results are promising and demonstrate a potential practical usefulness of the proposed methodology for automated generating of design rules.

**Key Words:** Machine Learning, Structural Design Knowledge Acquisition, Constructive Induction

<sup>1</sup>Assoc. Prof., Dept. of Urban Systems Engineering, Dept. of Systems Engineering, George Mason University, Fairfax, VA 22030

<sup>2</sup>Graduate Research Asst., Center for Artificial Intelligence, George Mason University, Fairfax, VA 22030

<sup>3</sup>Planning Research Corporation Chaired Professor of Computer Science and System Engineering and Director, Center for Artificial Intelligence, George Mason University, Fairfax, VA 22030

<sup>4</sup>Ph. D. Candidate, Dept. of Civil and Env. Engineering, Wayne State University, Detroit, MI 48202

<sup>5</sup>NSF Postdoctoral Research Associate, Center for Artificial Intelligence, George Mason University, Fairfax, VA 22030

## INTRODUCTION

Machine learning is a scientific discipline concerned with understanding computational principles of learning processes, and developing computer systems exhibiting learning capabilities. It represents an interdisciplinary research effort that draws upon results from such disciplines as computer science, cognitive science, and information systems.

Although efforts to build learning machines began in the early years of the computer era, major progress in understanding how to build practical computer systems with learning capabilities has occurred only relatively recently. In the last several years machine learning programs have been experimentally tried in a variety of domains, such as medical diagnosis, economics, agriculture, computer vision, financial decision making, and others.

The engineering disciplines are currently undergoing a paradigm shift. The analytical paradigm, based on the use of analytical tools, is rapidly becoming insufficient. At the same time, a new paradigm is emerging, founded on the use of knowledge-based decision support tools. However, the development and subsequent use of such tools requires the acquisition of formal knowledge, and decision rules are usually considered most convenient for engineering applications and therefore their acquisition is the subject of this paper.

Traditional methods of manual knowledge acquisition are insufficient to deal with complex engineering problems. Progress in using decision support tools has been delayed in part due to the difficulties of knowledge acquisition. The solution to this problem is *automated knowledge acquisition* based on the use of learning systems. But this has been difficult until recently because of a methodological gap between machine learning research and the problems of engineering design. This paper attempts to bridge this gap by developing a methodology for applying learning systems to the automated acquisition of engineering knowledge.

The paper also reports the results of an initial feasibility study on using two machine learning methods to this problem. These methods apply different forms of constructive induction, an advanced type of inductive learning that automatically searches for a suitable knowledge representation space. The study was conducted in the Machine Learning and Inference Laboratory at the Center for Artificial Intelligence at George Mason University in Fairfax, Virginia. The examples of optimal structural designs were prepared in the Intelligent Computer Laboratory of the Civil Engineering Department at Wayne State University, Detroit, Michigan.

There have been several previous studies on the application of machine learning to conceptual design knowledge acquisition. Gero (et al. 1989) (Mackenzie and Gero 1987) (McLaughlin and Gero 1987) used an experimental learning system based on a decision tree learning algorithm (ID3) to acquire architectural design knowledge. EXTASY, an expert system for analysis and design of microwave towers, has been developed with a learning component and used in experiments demonstrating the acquisition and use of design knowledge in conceptual design (Murlidharan et. al, 1992). Reich (1991, 1992 and Fenves 1992) implemented BRIDGER, an application of the clustering algorithm CLUSTER initially developed by Fisher (1987). BRIDGER was used to acquire bridge design knowledge. Reich and Fenves also studied knowledge acquisition for floor system design in buildings (Reich and Fenves, 1988) using an experimental system based on the learning system SOAR (Laird, et. al., 1986). Maher has been working on automated acquisition of preliminary design knowledge (Maher 1992, Maher and Li 1992, 1993) in which conceptual clustering is augmented by numerical methods of linear regression analysis and probabilistic approaches to pattern identification. A genetic algorithm was used by Maher and Kundu (1993) to develop a system for adaptive design. The same algorithm was also used by Grierson and Pak (1992) in a system for the optimization of configurations in the conceptual design of skeletal building structures and by Hajela for structural synthesis (1989). ROUGH, a learning system based on the theory of rough sets (Pawlak 1982, Ziarko 1989), was used by Arciszewski et al.

(1987) (Mustafa and Arciszewski 1992) for design knowledge acquisition in the area of structural design of wind bracings in tall buildings. Garrett and Ivezic (Ivezic and Garret 1993, Garret and Ivezic, to appear) describe an experimental learning system, NETSYN, based on a connectionist learning approach, for the acquisition of conceptual design knowledge. Also, Adeli and Yeah (1989) used a neural network to learn about engineering design. Milzner and Harbecke (1992) are involved in the development of an experimental learning system, LEAR, based on constructive induction, for learning design knowledge. This system, however, has not been used yet for experiments with engineering design examples. Whitehall, Stepp and Lu (1990) (Lu and Chen 1987) applied machine learning to design knowledge acquisition using several experimental learning systems. The AQ15 and AQ17 learning systems, employing the STAR methodology (Michalski 1983), were applied by Arciszewski and Dybala (1992) for learning design rules in the area of conceptual design of wind bracings in steel skeleton structures of tall buildings.

The application area for our study has been selected for significant technical reasons. At present, the analysis, design, and optimization of wind bracings in steel skeleton structures can be conducted using computer programs such as SODA (SODA is a Structural Optimization, Design and Analysis computer program for analyzing planar steel frames and trusses under static load. It was developed by Waterloo Engineering Software, Ontario, Canada). The use of these programs makes the design of wind bracings easier, but it still does not eliminate the need for the proper selection of a wind bracing type for a given design case. This selection must be based, as before, on the designer's experience. The computer program can produce a feasible locally optimal design of any type of wind bracing; however, this may not be the global optimum. For example, the computer program may produce a minimum-weight design for wind bracing in the form of a one-bay wide rigid frame in a twenty-story skeleton structure. This design may not be a global optimal design: much better weight and stiffness characteristics might be obtained with a truss wind bracing. The problem of selecting the proper type of wind bracing is particularly important when inexperienced designers use software tools for design and optimization; their lack of experience

may lead to feasible designs which could be significantly improved through simple changes in configuration.

For these reasons, research at Wayne State University on automated knowledge acquisition of wind bracings selection for steel skeleton structures was initiated in cooperation with Donald Grierson of Waterloo University, Ottawa, Canada. The knowledge acquired will eventually be used in a knowledge-based system which will be combined with SODA. This knowledge-based system will guide SODA users in the process of selecting the most appropriate types of wind bracings for their individual design cases. The research was initiated in 1986 by Arciszewski and Mustafa (Arciszewski and Ziarko 1987, Mustafa and Arciszewski 1989, Mustafa and Arciszewski 1992) in the Intelligent Computers Laboratory of the Civil Engineering Department at Wayne State University, Detroit.

The major novelty of the study reported here is that it concentrates on learning systems that have advanced capabilities for constructive induction. The research has two major objectives: 1) to determine the feasibility of applying constructive induction to acquiring knowledge of structural design, and 2) to determine the performance accuracy of constructive induction based learning systems in structural engineering in the case of the conducted study.

The feasibility of constructive induction in structural design knowledge acquisition was determined by the expert evaluation of machine generated rules which considered domain relevance and significance, while the performance accuracy of constructive induction-based learning systems was formally determined using two empirical error rates, as proposed for engineering applications (Arciszewski et al. 1992; Breiman et. al. 1984; Kibler and Langley 1988).

This paper reports the initial results of the feasibility study of constructive induction in structural design. It provides a brief description of the two forms of constructive induction

considered, including data-driven and hypothesis-driven constructive induction. The preparation of examples is discussed, and a detailed description of the knowledge acquisition process and its results are given. In conclusion, recommendations for further research are provided.

## **CONSTRUCTIVE INDUCTION**

### **Basic Concepts**

*Machine learning* studies mechanisms for creating or improving knowledge or skills by exploiting experience. Since learning is a fundamental characteristic of intelligent behavior, machine learning has been a focus of research in artificial intelligence since the beginnings of AI in the 1950's. The last several years have marked a period of great expansion and diversification of methods and approaches to machine learning. Most of the research has been oriented toward monostrategy methods that apply one primary type of inference and/or computational mechanism. Such methods include, for example, learning decision rules from examples. With the growing understanding of the capabilities and limitations of monostrategy methods, there has been an increasing interest in *multistrategy learning* systems that integrate two or more inference types and/or computational mechanisms. Such systems take advantage of the strengths of different learning strategies, and thus potentially can be applied to a much wider range of practical problems than monostrategy systems (Michalski and Tecuci, to appear 1993). One of the most important concerns of machine learning research is the dependence of learning programs on the initial attributes or predicates used to describe the data. The effectiveness of learning algorithms is very sensitive to the choice of representation space, in particular to the quality of the attributes and predicates used.

*Constructive induction* (CI) is a type of induction in which the formation of a new representation occurs during inductive learning (Michalski 1978). Therefore, instead of generalizing input information in the original description space, CI methods create a new space in which it may be much easier to construct a simple, accurate rule. This is possible because CI

methods modify the distribution of examples in the representation space making it easier to describe in the language of the inductive learner (nested axis-parallel hyperplanes in the case of decision trees, sets of axis parallel hyperplanes in the case of AQ). The two types of CI methods reported here are data-driven (DCI) and hypothesis-driven (HCI). In data-driven methods modifications to the representation space are based on relations found in the data such as attribute-correlations, while in hypothesis-driven methods rules generated from the data are analyzed and used to produce new attributes which make explicit patterns in these rules.

From the representational point of view, engineering applications provide a diverse set of learning problems. Some engineering applications have well defined concepts and require only a few attributes to adequately describe, while other applications, not as well understood, have complex descriptions, and potentially require modifications to the original representation space. The former already have been well studied, and are available in the form of domain theories (e.g. Theory of Elasticity, Theory of Plasticity, etc.). In the latter case, regularities are not obvious, due primarily to inadequate domain representations. Inadequacy in the domain representation may occur in three forms: 1) irrelevant attributes, 2) insufficient descriptors (hidden relationships between descriptors), or 3) a combination of the previous two. To deal with these problems, we investigated two methods of constructive induction: 1) data-driven constructive induction (DCI), which constructs new attributes based on input data analysis and application of various mathematical and logical operators, and 2) hypothesis-driven constructive induction (HCI), which builds new attributes by analyzing initially created inductive hypotheses, and detecting patterns in their descriptions.

### **Data-Driven Constructive Induction: DCI**

Most inductive learning programs perform "selective" induction, that is, they generate descriptions (rules, decision trees, etc.) that involve only attributes selected among those provided in the examples (Michalski, 1983). Thus, if the attributes used in the examples are weakly

relevant, or concepts are distributed among many attributes and are not explicit, the learned descriptions may be inaccurate and complex. It is possible, however, that although the original attributes may be of poor quality, there exist certain combinations or functions of these attributes that are highly relevant to the problem. For example, suppose there exist two sets of designs of wind bracings in a building described by the number of vertical and horizontal trusses. Sample data are shown in Table 1.

Table 1. Wind Bracings Described by Numbers of Vertical and Horizontal Trusses.

The rule which describes the characteristic of each class of building found by a selective program such as AQ14 is fairly complex:

Class1 <:: [Number of Vertical Trusses = 2] and [Number of Horizontal Trusses = 0] or  
[Number of Vertical Trusses = 1] and [Number of Horizontal Trusses = 1] or  
[Number of Vertical Trusses = 0] and [Number of Horizontal Trusses = 2]

Class2 <:: [Number of Vertical Trusses = 3] or  
[Number of Vertical Trusses = 2] and [Number of Horizontal Trusses = 1] or  
[Number of Vertical Trusses = 1] and [Number of Horizontal Trusses = 2] or  
[Number of Horizontal Trusses = 3]

The complexity of the rule is due to a mismatch between the type of rules learned by AQ (axis-parallel hyperplanes) and the distribution of examples in the representation space. By generating new attributes, the representation is enriched, and the rules constructed can be simpler and also more accurate. Various combinations of attributes using a variety of operations can be calculated. Useful combinations, which in this case involve addition, are kept. In this example, the total



number of trusses was calculated and found to be useful. This value was then retained and named Total Number of Trusses. The rules produced using this constructed attribute were:

Class1 <:: [Total Number of Trusses = 2]

Class2 <:: [Total Number of Trusses = 3]

where *Total Number of Trusses* is Number of Vertical Trusses + Number of Horizontal Trusses.

The DCI method is based on the generate and test paradigm. First, all numeric attributes are identified and all possible combinations are generated. Then, the pairwise operations to be performed on the individual pairs are selected from the list supplied by the user. With the attributes and operation selected, the values for the new attribute are calculated. The discriminatory power of these attribute values is then tested using the Attribute Quality Function (AQF). The AQF is the ratio defined below:

$$AQF = \frac{\textit{Unique examples}}{\textit{Total number of examples in class}}$$

where, unique examples are those examples that are not covered by any rule in other classes. The AQF is calculated for each class and for each attribute. A perfect discriminatory attribute, which alone discriminates one class from all other classes, will have an AQF value of 1. Possible AQF values range from 0 to 1. If a newly constructed attribute exceeds a predefined threshold for quality (quality thresholds are defined for each operator) then this new attribute is added to the list of available attributes and its calculated values are added to the training data. If the threshold for the AQF is set too low, then many possibly low quality attributes are generated. This abundance of low quality attributes can make the generation of simple, accurate rules more difficult. On the other hand if the AQF is set too high, new attributes which may be useful (to describe outlying examples, or to more simply describe large sets of examples) will be generated, but then discarded. An appropriate threshold can only be found by trial and error, but the range from 0.4 to 0.8 is generally sufficient.

A number of different operations are available to construct new attributes. These operations can be classified as either binary operators or multi-argument operators (functions). The binary group currently includes the Relational Operator, and a number of mathematical operators, including: Addition, Subtraction (absolute difference), Multiplication, and Integer-Division. Examples of each of these operations on fictitious data are shown in Table 2.

Table 2. Data-Driven Constructive Induction: Binary Operators.

The multi-argument class includes the following functions: Maximum, Minimum, Average, Least-Common, Most-Common, and #VarEQ(x). Except for the latter, these function are self-explanatory. #VarEQ(x) is a function which calculates the number of times the value x appears in an example. For a vector of binary-valued attributes, #VarEQ(1) counts the number of attributes that have a value of 1 in an example of a given class. Examples of these operations are shown in Table 3:

Table 3. Data-Driven Constructive Induction: Functional Operators.

The program has a default list of global functions, but allows the user to modify the list to fit the problem at hand. The default list of functions includes maximum, minimum, average, most frequent, least frequent, and #VarEQ(x).

### **Hypothesis-Driven Constructive Induction: HCI**

The hypothesis-driven constructive induction method extends the capabilities of a selective induction learning algorithm by constructing and using new attributes based on an analysis of the hypotheses generated. It relies on the capability of the selective algorithm to generalize from

examples to more general classification rules, given fixed representation space, i.e., a set of attributes and a set of concepts. The HCI method changes the representation space with respect to the set of attributes, or in general, descriptors. The set of concepts, as initially defined by a domain expert, remains unchanged. Figure 1 presents a diagram illustrating the HCI method (Wnek and Michalski 1993).

Figure 1. The HCI method for hypothesis-driven constructive induction.

In the implemented system, the input consists of training examples of one or more concepts, and background knowledge about the attributes used in the examples (a specification of their types and legal value sets). For the sake of simplicity, let us assume that the input consists of positive examples and negative examples of only one concept. If there are several concepts to learn, examples of each concept are taken as positive examples of that concept, and the set theoretical union of examples of other concepts are taken as negative examples of that concept.

The "Split of Examples" module randomly divides positive and negative training examples into primary, P, and secondary, S. The primary training set, P, is used for initial rule learning, the secondary set, S, for an evaluation of intermediate rules, and complete training set,  $P \cup S$ , is used for the final rule learning. The "Rule Learning" module induces a set of decision rules from the primary training set P, using the AQ15 inductive learning program (Michalski et al., 1986). The program employs the algorithm A9 for solving the general covering problem, which has been described in various sources, e.g., (Michalski, 1983). The "Rule Evaluation" module determines the performance of the rules on the secondary training set, S. The performance is measured in terms of predictive accuracy of the rules. The result is compared with the predefined threshold. If the performance accuracy does not satisfy the Stopping Condition, the rules are analyzed to

determine desirable changes in the representation space. The analysis of the hypothesis in the "Rule Analysis" module determines which of the original attributes are redundant, and which rules perform best for each decision class (or concept). In the "Representation Space Transformation" module, redundant attributes are removed from the representation space based on their presence (or lack) in generated rules. The best-performing rules are assembled into rulesets. The rulesets are assigned names, and treated as new attributes that extend the representation space. Training examples are projected into the new representation space ("Reformulation of Examples" module), and the inductive process is repeated. If the performance accuracy exceeds a predefined threshold, or chances for further improvement are estimated as being below a certain limit, final induction of decision rules is performed in the "Rule Learning" module from the complete training set.

## **KNOWLEDGE ACQUISITION PROCESS**

In the research reported, a relatively long and complex knowledge acquisition process was followed, and its major stages are briefly described here. However, this process incorporates several stages which could be avoided today, and therefore its simplifications and duration reduction are also discussed.

The knowledge acquisition process which was used consists of five major stages:

- 1. Development of Mathematical Models.** In this stage, the available general structural knowledge was used by Donald Grierson to develop a system of mathematical models for the analysis, design, and optimization of steel structures, which could be consistently implemented in computer programs. Modeling was initiated in the early sixties at Waterloo University, and the majority of work was completed in the late eighties (Grierson 1989, Grierson and Cameron 1989).

**2. Implementation of Models.** This stage involved the development of the computer program, SODA, for the analysis, design, and optimization of steel structures. This was completed in the mid-eighties by Donald Grierson at Waterloo Engineering Software.

**3. Building the Knowledge Representation.** The work included the identification of relevant attributes describing wind bracings in steel skeleton structures and the determination of their values. The work was initiated in the early seventies by Tomasz Arciszewski at Warsaw Technical University for the purposes of wind bracings classification and continued at Wayne State University in Detroit for the purpose of wind bracings conceptual design (Arciszewski 1985).

**4. Preparation of Examples.** This stage involved the preparation of a collection of 336 examples of SODA-generated minimum-weight wind bracing designs of various types. It was initiated in 1989 by Mohamad Mustafa and Tomasz Arciszewski at Wayne State University, and took approximately two years to complete.

**5. Constructive Induction of Decision Rules from Examples.** In this stage, two experimental learning systems, based on data-driven and hypothesis-driven constructive induction, were used to produce decision rules. The work was conducted at the Center for Artificial Intelligence at George Mason University in 1992, and it took several weeks to complete induction and to interpret results.

Stage one in the knowledge acquisition process was concerned with the development of deep models. In stage two, a simulation model for a wind bracing was produced. In stage three, relevant attributes and their values were proposed. Stage four, Preparation of Examples, can be considered as knowledge deduction from the deep model through the use of the simulation model. In this stage, specific examples are generated through deduction applying the general deep knowledge. In the last stage, design rules are learned from examples using constructive induction methods.

In the case of research on conceptual design of wind bracings in tall buildings which ultimately evolved into work on automated design knowledge acquisition, the first three stages could not be avoided and therefore they were incorporated in our process. However, in the other areas of structural engineering, mathematical models and computer programs based on them are easily available. Therefore, stages one and two could be avoided, and this could significantly reduce time to complete a similar project in the future. Also, building the knowledge representation has been a long process in our case, but at the beginning its objectives were different than automated knowledge acquisition. Today this process could be completed in several weeks, if necessary. Preparation of examples took approximately two years to complete, but this was done by a structural engineer working only part time on this project. That time could be significantly reduced to approximately three months of a full time work of a single structural designer.

In stage five, Constructive Induction of Decision Rules from Examples, two knowledge induction processes were conducted:

1. Generation of decision rules from examples using data-driven constructive induction, and
2. Generation of decision rules from examples using hypothesis-driven constructive induction.

The knowledge acquisition process is shown in Fig. 2. In this process, SODA is used to generate examples, and two experimental learning systems, based on data-driven and hypothesis-driven constructive induction, are used to induce decision rules.

Figure 2. Process of Learning Design Rules.

## BUILDING THE KNOWLEDGE REPRESENTATION

An eight-attribute description of the design problem and the wind bracing itself was developed for our project (Mustafa 1989). The attributes used are sufficient to describe various types of planar frame, truss, and truss-frame bracings which are appropriate for buildings in the six to thirty-story height range considered in our study. These attributes are based on a general description of wind bracings in tall buildings proposed by Arciszewski (1985) and used by Mustafa and Arciszewski (1992) in earlier machine learning experiments in the area of knowledge acquisition of conceptual wind bracing design. The individual attributes and their values are given in Table 4.

The first three attributes, *Number of Stories*, *Bay Length*, and *Wind Intensity Factor*, describe the design case (design requirements) considered. The Wind Intensity Factor characterizes the wind exposure of a tall building and is location dependent. Attributes No. 4 through No. 7 describe the structural system of wind bracing itself, while the last attribute, No. 8, *Unit Steel Weight*, identifies the nominal value of the relative unit weight of the steel structural system of a wind bracing described by attributes one through seven. This relative unit steel weight is determined considering all normalized unit weights of various types of wind bracings of the same height designed under identical conditions.

Table 4. Attributes and Their Values.

The decision rules obtained are divided into four classes corresponding to the values of the decision attribute *Unit Steel Weight*. Values of the unit weight are specified in the examples as low, medium, high, and infeasible when SODA could not produce a wind bracing under the given assumptions which would satisfy all design requirements. Therefore, the decision rules which

specify designs with low unit weights are called *Recommendation Rules*. Similarly, decision rules which produce medium unit weights are called *Standard Rules*, and rules which produce high unit weight are called *Avoidance Rules*. Rules producing infeasible wind bracings are called *Infeasibility Rules*.

## **PREPARATION OF EXAMPLES**

In earlier research on machine learning about design of wind bracings in tall buildings (Mustafa and Arciszewski 1992), a collection of examples of various designs was prepared by human experts. The results of learning were found to be only partially satisfactory. Not all decision rules were correct from the structural point of view, and their interpretation was difficult. The problem is believed to be due mostly to an insufficient number of examples (165), and the possible misclassification of some examples. While knowledge acquisition techniques are improving it was decided to follow a different route in which examples of optimal wind-bracing designs based on computer models be used. In this way, a larger number of examples could be produced and their quality monitored.

Therefore, decision rules were learned from a collection of 336 examples of minimum weight (optimal) designs of wind bracings in steel skeleton structures of tall buildings. Each example has three major components: 1) a description of the building for which a given bracing is intended (design case or design requirements), 2) a description of the wind bracing structural system, and 3) an evaluation of the unit steel weight of a given wind bracing for the design case considered. Therefore, each example relates the design requirements to the selection of components of a wind bracing structural system and the unit steel weight of this system. Machine learning is used then to produce decision rules which explain how design requirements can be satisfied through the proper selection of individual components of a wind bracing structural system in order to minimize its unit weight.



Examples were prepared by Mohamad Mustafa (1989) as part of his doctoral research on an engineering methodology of automated knowledge acquisition. All detailed design assumptions regarding loads, dimensions, steel grade, etc., were determined in cooperation with practicing structural designers and are reported in Mustafa (1993). All examples were prepared under identical design assumptions for a three-bay skeleton structure of a tall building. Actual minimum-weight designs were produced using SODA. All designs were verified by Mustafa, who is a structural designer with the Wayne County Structural Division.

### **DATA-DRIVEN CONSTRUCTIVE INDUCTION**

A number of experiments were performed with DCI. In these experiments the expert selected the relationship, addition, subtraction and multiplication operators as being potentially useful. These operators produced two new attributes (in separate experiments):  $x_1 * x_2$  (Bay\_length \* #stories) and  $x_5 - x_6$  (#bays - #vertical trusses). Rules generated from datasets extended by these new attributes resulted in rules which were slightly more complex (more rules per class) and approximately the same accuracy. However, these new attributes lack a meaningful interpretation (bay\_length \* #stories has no clear units). For this reason these generated attributes were discarded. The process of analyzing these automatically generated attributes, however, spurred the expert to generate a new attribute called *Demand*, which is defined as:

$$Demand = \frac{\text{Number of Stories} * \text{Wind Intensity}}{\text{Bay Length}}$$

The new attribute Demand can be interpreted as a measure of demand for bracings: it increases with the height of the building (measured by attribute No. 1, Number of Stories) and the importance factor which is associated with the wind exposure (represented by attribute No. 3, Importance Factor) and decreases with the width of the building (measured by attribute No. 2, Bay Length). In the collection of examples considered, the new attribute Demand has the domain

(0.214 .. 1.665). This domain was arbitrarily divided into several subranges, and each subrange was given a name:

1. Subrange 0.214 .. 0.500 – very low demand
2. Subrange 0.500 .. 0.780 – low demand
3. Subrange 0.780 .. 1.060 – average demand
4. Subrange 1.060 .. 1.340 – high demand
5. Subrange 1.340 .. 1.665 – very high demand

Seven *Recommendation Rules*, thirteen *Standard Rules*, ten *Avoidance Rules*, and one *Infeasibility Rule* have been obtained. All these decision rules, with the exception of *Standard Rules*, are presented and their domain interpretation is provided. *Standard Rules* are correct, but their number and complexity exclude the possibility of discussion here. Decision rules are shown in parentheses as they were produced by the system. These rules could be directly used in a knowledge based system for making predictions regarding unit steel weight for various structural configurations of wind bracings. However, these rules should not be understood as rules which explain how to optimally satisfy design requirements. The obtained decision rules were interpreted using additional common sense heuristics which are also included. As a result design interpretations were produced. These interpretations could be used by a novice designer to learn about the structural shaping of wind bracings.

The decision rules given below were computer generated. The interpretation of these rules as an evaluation of various structural configurations from the point of view of unit weight, used the following heuristics:

1. Avoid designing wind bracings with high unit weight.
2. Design wind bracings with low unit weight.
3. Never design wind bracings which are infeasible.

The following *Avoidance Rules* (AR) were produced:

AR1: IF (Number of Bays IS **1 or 2**) &  
(Number of Vertical Trusses IS **0**) &  
(Demand IS **very low**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

If demand for bracing is very low, then avoid designing a wind bracing in the form of a single or double one-bay rigid frame without vertical trusses.

AR2: IF (Joints ARE **rigid or mixed**) &  
(Number of Horizontal Trusses IS **0 or 2**) &  
(Demand IS **very low**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

If demand for bracing is very low, then avoid designing a wind bracing in the form of a rigid frame, or in the form of a rigid frame with two horizontal trusses.

AR3: IF (Joints ARE **mixed**) &  
(Number of Bays IS **1 or 2**) &  
(Demand IS **very low**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

If demand for bracing is very low, then avoid designing a wind bracing in the form of a one-bay bracing with mixed joints (braced rigid frame) or in the form of two braced rigid frames.

AR4: IF (Number of Bays IS **1**) &  
(Number of Vertical Trusses IS **0**) &  
(Number of Horizontal Trusses IS **1**) &  
(Demand IS **very low**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

If demand for bracing is very low, then avoid designing a wind bracing in the form of a one-bay rigid frame with one horizontal truss.

AR5: IF (Number of Bays IS **1**) &  
(Number of Vertical Trusses IS **0**) &  
(Demand IS **average**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

If demand for bracing is average, then avoid designing a wind bracing in the form of a single bay rigid frame.

AR6: IF (Importance Factor IS **high**) &  
(Joints ARE **rigid**) &  
(Demand IS **average**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

If demand for bracing is average and the building is located in a high wind intensity zone, then avoid designing wind bracings with rigid joints only without any trusses.

AR7: IF (Number of Stories IS **12**) &  
(Bay Length IS **20**) &  
(Joints ARE **mixed**) &  
(Number of Bays IS **2**) &  
(Number of Horizontal Trusses IS **3**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

Avoid designing two-bay rigid frames with three horizontal trusses for narrow twelve-story buildings.

AR8: IF (Number of Stories IS **30**) &  
(Joints ARE **mixed**) &  
(Number of Bays IS **2**) &  
(Number of Horizontal Trusses IS **1 or 2**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

Avoid designing a thirty story building with wind bracings in the form of two-bay rigid frames with one or two horizontal trusses.

AR9: IF (Joints ARE **mixed**) &  
(Number of Bays IS **1**) &  
(Number of Horizontal Trusses IS **1**) &  
(Demand IS **average**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

If demand for bracing is average, then avoid designing wind bracings in the form of a single-bay rigid frame with one horizontal truss.

AR10: IF (Number of Stories IS **24**) &  
(Number of Bays IS **3**) &  
(Number of Horizontal Trusses IS **3**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

Avoid designing a 24-story building with three-bay wind bracing with three horizontal trusses (a three-bay rigid frame with three horizontal trusses).

The following seven *Recommendation Rules* (RR) were obtained:

RR1: IF (Number of Vertical Trusses IS **1..3**) &  
(Demand IS **very low or low or average**)  
THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

If demand is very low, low, or average, then design wind bracings with vertical trusses.

RR2: IF (Number of Stories IS **30**) &  
(Number of Vertical Trusses IS **1 or 2**) &  
(Number of Horizontal Trusses IS **1..3**)  
THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

For thirty-story buildings, design wind bracing systems using combinations of vertical and horizontal trusses.

RR3: IF (Number of Bays IS **2 or 3**) &  
(Number of Horizontal Trusses IS **1..3**) &  
(Demand IS **very low**)  
THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

If demand for bracing is very low, design two- or three-bay wind bracings with horizontal trusses.

RR4: IF (Number of Stories IS **30**) &  
(Number of Vertical Trusses IS **1**)  
THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

Design thirty-story buildings with wind bracings containing one vertical truss.

RR5: IF (Number of Vertical Trusses IS **3**)  
THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

Design wind bracings with three vertical trusses.

RR6: IF (Number of Vertical Trusses IS **3**) &  
(Number of Horizontal Trusses IS **3**) &  
(Demand IS **very low**)  
THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

When demand for bracing is very low, then design wind bracings with three vertical and three horizontal trusses. (This case would very rarely occur because wind bracing with three vertical trusses normally do not have any additional horizontal trusses.)

RR7:           IF       (Joints ARE **rigid**) &  
                  (Number of Bays IS **2**) &  
                  (Demand IS **high**)  
          THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

When demand for bracing is high, then design wind bracings in the form of two single one-bay rigid frames.

In the decision rules produced, the attribute “Wind Intensity Factor” has not been used. It is a surprising result, because in structural engineering the location of a building and its related wind exposure are usually considered significant when studying various types of wind bracings. In the case of our experiments, this attribute has been found to be redundant in the conceptual design of wind bracings. However, this result is valid only in the context of the 323 examples used, and can be explained by the fact that all wind bracings considered were in buildings with relatively low wind intensity values: buildings of thirty stories or less.

Interestingly, for thirty-story buildings two recommendation rules were produced: RR2 and RR4. Both rules say that at least one vertical truss should be used in the wind bracing. The first one is relatively specific and deals with the selection of both horizontal and vertical trusses, while the second one is more general in this respect and specifies that only one vertical truss in bracing should be used. The two decision rules are consistent, but intersecting.

The last decision rule, RR7, is incorrect. It has been produced because of an error in the input data. Example No. 298 had an incorrectly entered value of the decision attribute - low unit weight instead of high unit weight. Therefore, a recommendation rule instead of an avoidance rule was produced. This decision rule is shown and discussed here to demonstrate how sensitive the learning system is sometimes to incorrect examples.

Only one *Infeasibility Rule* (IR) was produced:

```

IR1:      IF      (Joints ARE rigid or mixed) &
              (Number of Bays IS 1) &
              (Demand IS high)
              THEN wind bracing will be infeasible.

```

Design Interpretation:

When demand for bracing is high, never design wind bracings in the form of a single one-bay structural system with rigid or mixed joints.

## **HYPOTHESIS-DRIVEN CONSTRUCTIVE INDUCTION**

The learning system conducted a three-stage knowledge acquisition process. In the first stage, abstraction of the knowledge in the form of examples was performed and the representation space was reduced. Attribute No. 3, Wind Intensity Factor, was eliminated. This result is not entirely unexpected, because wind intensity for low ( $\leq 30$  story) buildings is rarely a decisive factor in structural shaping: the configuration of structural components and connections in a wind bracing. In the second stage of knowledge acquisition, the system conducted concretion of knowledge and constructed a new attribute with five values. This new attribute, called the Constructed Attribute, or CA, is defined as follows:

```

IF      (Number of Stories IS 6) &
        (Number of Bays IS 1 or 2) &
        (Number of Vertical Trusses IS 0) &
        (Number of Horizontal Trusses IS 0..2)
        OR
        (Number of Stories IS 6) &
        (Bay Length IS 30) &
        (Number of Vertical Trusses IS 0) &
        (Number of Horizontal Trusses IS 0..2)
        OR
        (Number of Stories IS 6) &
        (Bay Length IS 30) &
        (Number of Bays IS 1 or 2) &
        (Number of Vertical Trusses IS 0)
THEN    CA = 1

```

```

IF      (Number of Stories IS 12..30) &
        (Number of Bays IS 3) &
        (Number of Vertical Trusses IS 0) &
        (Number of Horizontal Trusses IS 0..2)
        OR
        (Number of Stories IS 12..24) &
        (Bay Length IS 30) &
        (Joints ARE rigid or mixed) &
        (Number of Bays IS 1 or 2) &
        (Number of Horizontal Trusses IS 0 or 2 or 3)
        OR
        (Number of Stories IS 18 or 24) &
        (Joints ARE mixed) &
        (Number of Horizontal Trusses IS 1 or 3)
THEN    CA = 2

IF      (Number of Stories IS 6..24) &
        (Number of Bays IS 2 or 3) &
        (Number of Vertical Trusses IS 1..3)
        OR
        (Number of Stories IS 12..30) &
        (Joints ARE hinged) &
        (Number of Horizontal Trusses IS 1..3)
THEN    CA = 3

IF      (Number of Stories IS 30) &
        (Joints ARE rigid or mixed) &
        (Number of Bays IS 1)
THEN    CA = 4

IF      (none of the above rules is satisfied)
        OR
        (more than one rule is satisfied)
THEN    CA = 5

```

All values of the Constructed Attribute have a structural engineering meaning and can be explained in the terms of structural shaping of wind bracings. For example, the value **1**, (CA = 1) can be interpreted in the following way:



*A six-story rigid frame with the following structural characteristics:*

(Number of Stories IS **6**) &  
(Number of Vertical Trusses IS **0**)

*(1) a single one-bay or two one-bay structural system with or without one or two horizontal trusses*

(Number of Bays IS **1 or 2**) &  
(No H. Trusses IS **0..2**)

*OR*

*(2) with a wide bay and with or without one or two horizontal trusses*

(Bay Length IS **30**) &  
(No H. Trusses IS **0..2**)

*OR*

*(3) with a wide bay and as a single one-bay or two one-bay structural system*

(Bay Length IS **30**) &  
(Number of Bays IS **1 or 2**)

In the third stage of knowledge acquisition, the system produced four classes of decision rules, including five *Avoidance Rules*, five *Standard Rules*, three *Recommendation Rules*, and one *Infeasibility Rule*. All decision rules, with the exception of *Standard Rules*, are presented and their design interpretation provided:

*Avoidance Rules (AR):*

AR1: IF (CA IS **1**)  
THEN *a high unit weight of bracing should be expected*

Design Interpretation:

Avoid designing wind bracings for which the value of the constructed attribute CA is equal to 1.

AR2: IF (Number of Bays IS **1 or 3**) &  
(Number of Vertical Trusses IS **0**) &  
(Number of Horizontal Trusses IS **1**) &  
(CA IS NOT **2**) &  
(CA IS NOT **4**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

Avoid designing a one- or three-bay wind bracing in the form of a rigid frame, with one horizontal truss and make sure that the value of constructed attribute CA is neither two nor four.

AR3: IF (Number of Stories IS **12**) &  
(Bay Length IS **20**) &  
(Joints ARE **mixed**) &  
(Number of Bays IS **2**) &  
(Number of Horizontal Trusses IS **3**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

Avoid designing twelve-story buildings with a narrow bay with wind bracings in the form of two one-bay rigid frames and three horizontal trusses.

AR4: IF (Number of Stories IS **18**) &  
(Number of Vertical Trusses IS **0**) &  
(Number of Horizontal Trusses IS **0**) &  
(CA IS NOT **2**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

Avoid designing eighteen-story buildings with wind bracings in the form of rigid frames and make sure that the constructed attribute CA is not equal to two.

AR5: IF (Number of Stories IS **18**) &  
(Joints ARE **mixed**) &  
(Number of Bays IS **1**) &  
(CA IS NOT **2**)  
THEN *a high unit weight of bracing should be expected.*

Design Interpretation:

Avoid designing eighteen-story buildings with wind bracings in the form of a single one-bay rigid frame with horizontal truss or trusses and with the constructed attribute CA not equal to two.

Three *Recommendation Rules* (RR) were produced:

RR1: IF (CA IS 3)  
THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

In designing wind bracings in tall buildings, select bracings which are described by the constructed attribute CA equal to 3.

RR2: IF (Bay Length IS 20) &  
(Joints ARE **hinged**)  
THEN *a low unit weight of bracing should be expected.*

Design Interpretation:

Use truss bracings for narrow bay buildings.

RR3: IF (Number of Stories IS 12..30) &  
(Bay Length IS 20) &  
(Number of Bays IS 1 or 3) &  
(Number of Horizontal Trusses IS 0 or 3) &  
(CA IS NOT 2) &  
(CA IS NOT 4)  
THEN *a low weight of bracing should be expected.*

Design Interpretation:

Design wind bracings for twelve-, eighteen-, and thirty-story buildings with narrow bay in the form of one- or three-bay structural systems without or with three horizontal trusses and make sure that the value of constructed attribute CA is neither two nor four.

A single *Infeasibility Rule (IR)* was produced:

IR1: IF (CA IS 4)  
THEN *the wind bracing will be infeasible.*

Design Interpretation:

Never design wind bracings if the constructed attribute CA is equal to four.

This is equivalent to the rule:

IR1: IF (Number of Stories IS 30)  
(Joints ARE **rigid or mixed**) &  
(Number of Bays IS 1)  
THEN *the wind bracing will be infeasible.*

Design Interpretation:

In the case of a thirty-story building, never design wind bracings in the form of a single one-bay structural system with rigid or mixed joints.

## **PERFORMANCE ANALYSIS**

One of this paper's objectives is to investigate the performance of constructive induction-based learning systems in the area of structural design knowledge acquisition. This performance can be formally measured by various empirical error rates, which are determined through tests. In each test, a learning system uses a given body of examples to make predictions about other known examples which have not been included in its input. Each test can be then compared to a real-life situation, when a designer uses a decision support system to predict the structural attributes of a wind bracing to minimize its weight. Therefore, empirical error rates are highly relevant to both machine learning research, which is concerned with the performance of learning systems, and to structural design, which is concerned with the optimal decision making.

Two empirical error rates were used: 1) the overall empirical error rate, and 2) the omission error rate. The overall empirical error rate was used because it provides the most general evaluation of performance of a learning system and the knowledge acquired. Also, it has a simple interpretation, convincing for structural designers. The omission empirical error rate is also important, because it measures the degree to which the learning system, using knowledge acquired, fails to recognize cases belonging to individual categories of the decision attribute.

The overall empirical error rate is defined (Weiss and Kulikowski, 1991; Arciszewski et al., 1992) as:

$$E_{ov} = \frac{\text{Number of errors}}{\text{Number of tests}}$$

where: *Number of errors* is the number of misclassifications on test examples,  
*Number of tests* is the number of classification tests.

The omission empirical error rate is defined (Arciszewski et al., 1992) as:

$$E_{om} = \frac{\sum_{i=1}^n E_{om}^i}{n}$$

where:  $n$  is the number of classes

$$E_{om}^i = \frac{\text{Number of omission errors for class "i"}}{\text{Number of tested examples of class "i"}}$$

*Number of omission errors for class "i"* is the number of errors when a positive example is classified as a negative one

*Number of tested examples of class "i"* is the number of classification tests for class "i"

Both error rates were calculated for the entire collection of examples using the leave-one-out resampling method (Weiss and Kulikowski, 1991). These error rates were determined for "traditional" induction, based on the use of the AQ15 algorithm, and for two experimental learning systems based on data-driven and hypothesis-driven constructive induction. Individual error rates are shown in the Table 5. There is a significant improvement in performance (more than 50 percent) between the system based on "traditional induction" and systems based on constructive induction. When the error rate is considered, no performance difference between both types of constructive induction is observed. However, for the omission error rate, data-driven constructive induction produced marginally better results (3% difference), but it would be premature to make any conclusions about it since this may change as the research progresses.

Table 5. Comparison of Empirical Error Rates for Various Learning Systems.

## CONCLUSIONS

The results demonstrate that the use of constructive induction in structural design knowledge acquisition is feasible. The decision rules produced are relatively simple and their structural interpretation is possible, although not always easy, particularly when complex constructed attributes are used.

The changes in the representation space, i.e., the introduction of constructed attributes, were found to be acceptable to human experts. These changes could stimulate the process of human learning, but much more research is necessary to determine how constructive induction could be used in human learning.

The five-stage knowledge acquisition process used in this research is complete and should be sufficient for practical purposes. However, it is applicable only to those structural design domains where mathematical and simulation models are available, or can be easily produced. The knowledge representation stage was found to be particularly difficult. It required extensive study and the cooperation of experts. The identification of relevant attributes and their nominal values began in the early seventies, and these attributes have undergone numerous changes and modifications before a final acceptable set was produced. Including mathematical modeling, simulation and knowledge representation, the entire process of knowledge acquisition took about thirty years, although its last two stages, Knowledge Deduction and Knowledge Induction, were completed in about two years.

However, based on our experience, it can be estimated, that the entire process of knowledge acquisition could be conducted in approximately three years in the other structural engineering

domains in which mathematical models as well as analytical computer programs are available, and descriptors are known.

The learning system based on data-driven constructive induction produced ten *Recommendation Rules*, thirteen *Standard Rules*, seven *Avoidance Rules*, and one *Infeasibility Rule*. The learning system based on hypothesis-driven constructive induction produced four *Recommendation Rules*, five *Standard Rules*, three *Avoidance Rules*, and one *Infeasibility Rule*, respectively. The rules produced by the two systems are different, but not inconsistent. An analysis of advantages and disadvantages of rules produced by individual systems is possible, but it has not been conducted because the results would be subjective. However, an objective analysis of performance of learning systems based on the two forms of constructive induction was completed.

The performance analysis shows that both forms of constructive induction are more effective in terms of empirical error rates than traditional selective induction based on the AQ15 learning algorithm. An approximately 50 percent performance improvement is considered significant in machine learning, and should be accepted as such in civil engineering. The differences in performance between two systems based on different forms of constructive induction are below 5 percent, and they are obviously insignificant. Therefore, both forms of constructive induction should be considered equivalent from the performance point of view in the area of structural design knowledge acquisition. It would be desirable to produce and analyze learning curves for empirical error rates for both systems, to learn more about their performance in a multistage automated knowledge acquisition process, and this work is planned.

The feasibility study was conducted in the area of structural design knowledge acquisition, and therefore all conclusions produced are valid only in this area. However, it could be inferred by

analogy that similar results, in terms of clarity of decision rules and good performance, should be expected in other areas of civil engineering.

Machine learning research has already reached a fair level of maturity, and has resulted in various experimental and commercial learning systems. These systems could be used in civil engineering to improve productivity in knowledge acquisition and the development of knowledge-based decision support systems. However, the application of learning systems has been difficult because of the lack of a method of their use. This paper proposes such a method. The results from the case study demonstrate a high potential and its practical usefulness to the automated generation of design rules.

### **Acknowledgments**

The authors thank Ken Kaufman and other graduate students of the Center for AI at George Mason University for their comments and assistance in the experiments reported here, and the reviewers for their unusually detailed and helpful comments and suggestions. The contribution of Dr. Yoram Reich of the University of Tel Aviv in Israel is also acknowledged. We are grateful for the cooperation of Waterloo Engineering Software, Ontario, Canada, which provided SODA, the software used in the preparation of examples.

This research was conducted in the Center for Artificial Intelligence at George Mason University. The Center's research is supported in part by the Defense Advanced Research Projects Agency under Grant No. N00014-91-J-1854, administered by the Office of Naval Research, and the grant No. F49620-92-J-0549, administered by the Air Force Office of Scientific Research, in part by the Office of Naval Research under Grant No. N00014-91-J-1351, and in part by the National Science Foundation under Grants No. IRI-9020266 and CDA-9309725.



## APPENDIX I. REFERENCES

Adeli, H. and Yeah, C., (1989). "Perception Learning in Engineering Design," *Microcomputers in Civil Engineering*, No. 4.

Arciszewski, T., Dybala, T. and Wnek, J., (1992). "A Method for Evaluation of Learning Systems," *Journal of Knowledge Engineering "Heuristics,"* Vol. 5, No. 4, pp. 22-31.

Arciszewski, T. and Dybala, T., (1992). "Evaluation of Learning Systems: A Method and Experimental Results," *Report*, Center for Artificial Intelligence, George Mason University.

Arciszewski, T. and Mustafa, M., (1989). "Inductive Learning Process: The User's Perspective," in *Machine Learning*, R. Forsyth (Ed.), Chapman and Hall, pp. 39-61.

Arciszewski T. and Ziarko W., (1987). "Adaptive Expert System for Preliminary Engineering Design," *Revue Internationale de CFAO et D'Intographie*, Vol. 2, No. 1.

Arciszewski, T., Mustafa, M. and Ziarko, W., (1987). "A Methodology of Design Knowledge Acquisition for Use in Learning Expert Systems," *Int. J. Man-Machine Studies*, Academic Press Limited, 27, pp. 23-32.

Arciszewski, T., (1985). "Decision Making Parameters and their Computer-Aided Analysis for Wind Bracings in Steel Skeleton Structures," *Advances in Tall Buildings*, Van Nostrand Publishing Company.

Fisher, D. (1987), "Knowledge Acquisition via Incremental Conceptual Clustering", *Journal of Machine Learning*, No. 2. p. 130-172.

Garrett, J. H. and Ivezic, N., (in print). "A Neural Network Approach for Acquiring and Using Synthesis Knowledge," *Proceedings of the Japan-U.S. Workshop on Expert Systems and AI Applications in Civil and Structural Engineering*, 25-26 August, 1992, Tokyo.

Garrett, J. H. and Ivezic, N., (1992). "A Neural Network Approach for Acquiring and Using Synthesis Knowledge", *Intelligent Engineering Through Artificial Neural Networks*, Vol. 2, C.H. Dagli, L.I. Burke and Y.C. Shin, eds. ASME Press, New York. pp. 767-772.

Gero, J.S., Mackenzie, C.H., and McLaughlin, S., (1989). "Learning from Optimal Solutions to Design Problems," *Proceedings of NATO ASI Conference on Optimization and Decision Support Tools in Civil Engineering*, Edinburgh.

Grierson, D.E., (1989). "Computer-Automated Optimal Design for Structural Steel Frameworks," *Proc. of NATO ASI Conf. on Optimization and Decision Support Systems in Civil Engineering*, Edinburgh.

Grierson, D.E. and Cameron, G.E., (1989). "Microcomputers -Based Optimization of Steel Structures in Professional Practice," *Microcomputers in Civil Engineering*, Elsevier Publishing, Vol 4. pp. 289-296.

Grierson, D.E., Pak, W.H., (1992). "Discrete Optimal Design Using a Genetic Algorithm," *Proceedings of NATO Conference on Topology Design of Structures*, Portugal.

Hajela, P., (1989). "Genetic Algorithms in Automated Structural Synthesis," *Proc. of NATO ASI Conf. on Optimization and Decision Support Systems in Civil Engineering*, Edinburgh.

Ivezic, N. and J.H. Garret, Jr. (1993). "NETSYN: Neural Network-based Support for Synthesis", *In Proceedings of the Fifth International Conference on Computing in Civil Engineering*. American Society of Civil Engineers. L. Cohen, ed. pp. 1440-1448. June 7-9.

Ivezic, N. and J.H. Garret, Jr. (in print). "A Neural Network-based Machine Learning Approach for Supporting Synthesis". submitted for publication to *Artificial Intelligence in Engineering Design, Analysis and Manufacturing (AI EDAM)*.

Laird, J.E., Rosenbloom, P.S., and Newell, A., (1986). "Chunking in SOAR: The Anatomy of A General Learning Mechanism", *Journal of Machine Learning*, No. 1, p.11-46.

Lu, S.C-Y. and Chen, K., (1987). "A Machine Learning Approach to the Automatic Synthesis of Mechanistic Knowledge for Engineering Decision Making," *Journal Artificial Intelligence in Design and Manufacturing*, Vol. 1, No. 2.

Mackenzie, C.A. and Gero, J.S., (1987). "Learning Design Rules from Decisions and Performances," *Artificial Intelligence in Engineering*, Vol. 2, No. 1.

Maher, M.L., (1992). "Automated Knowledge Acquisition of Preliminary Design Concepts," *Proceedings of the ASCE Conference for Computing in Civil Engineering*, Dallas, Texas. pp. 975-982.

Maher, M.L. and Li, H., (1992). "Automatically Learning Preliminary Design Knowledge from Design Examples," *Microcomputers in Civil Engineering*, Vol. 7, No. 1. pp. 73-80.

Maher, M.L. and Li, H. (1993). "Adapting Conceptual Clustering for Preliminary Structural Design", *Proceedings of the 9th ASCE Conference of Computing in Civil Engineering*, Anaheim, CA, pp 1432-1439.

Maher, M.L. and Kundu, S. (1993). "Adaptive Design Using a Genetic Algorithm", in Gero, J.S. and Sudweeks, F. (eds.) *Preprints Formal Design Methods for CAD*, Key Centre of Design Computing, University of Sydney, pp 211-228.

McLaughlin, S. and Gero, J.S., (1987). "Acquiring Expert Knowledge from Characterized Designs," *AIEDAM*, Vol. 1, No. 2.

Michalski, R.S., (1978). "Pattern Recognition as Knowledge-Guided Computer Induction," *Report*, Computer Science Dept., University of Illinois, Urbana.

Michalski, R.S. (1983). "A Theory and Methodology of Inductive Learning," In *Machine Learning: An Artificial Intelligence Approach*, Vol. I, R.S. Michalski, J.G. Carbonell and T.M. Mitchell (Eds.), Morgan Kaufmann, Los Altos, CA.

Michalski, R.S., (to appear 1993). "Inferential Theory of Learning: Developing Foundations for Multistrategy Learning," *Machine Learning: A Multistrategy Approach*, Vol. IV, R.S. Michalski and G. Tecuci (Eds.), Morgan Kaufmann, San Mateo, CA. (An earlier version published in *Reports of Machine Learning and Inference Laboratory*, MLI 92-3, Center for AI, George Mason University, 1992).

Michalski, R.S. and Tecuci, G., (to appear 1993). *Machine Learning: A Multistrategy Approach*, Vol. IV, Morgan Kaufmann Publishers, San Mateo, CA.

Milzner, K. and Harbecke, A., (1992). "Incremental Learning for Improved Decision Support in Knowledge Based Design Systems," *Proceedings of the Second International Conference on Artificial Intelligence in Design 1992*, J.S. Gero (Ed.), Pittsburgh.

Murlidharan, T.L., Aravind, H.B., Suryakumar, G.V, Raman, N.N., (1991). "Expert Tower Analysis and Design System II: Search Strategies and Learning", *Journal of Computing in Civil Engineering*, Vol, 5.No. 2, pp. 193-210.

Mustafa, M., (1989). "Engineering Methodology of Automated Knowledge Acquisition: Structural Application," *Ph. D. Proposal*, Civil Engineering Department, Wayne State University, Detroit.

Mustafa, M., (1993). "Methodology of Inductive Learning: Structural Engineering Applications", Ph.D. Dissertation, Civil Engineering Department, Wayne State University, Detroit, MI, 48202.

Mustafa, M. and Arciszewski T., (1992). "Inductive Learning of Wind Bracing Design for Tall Buildings," in *Knowledge Acquisition in Civil Engineering*, T. Arciszewski and L. Rossman (Eds.), the American Society of Civil Engineers.

Pawlak, Z., (1982). "Rough Sets," *Intl. Journal of Computer and Information Sciences*, No. 11, Vol. 5, pp. 341-356.

Reich, Y., (1991). "Design Knowledge Acquisition: Task Analysis and A Partial Implementation," *Knowledge Acquisition*, Vol. 3, No. 3, pp. 237-254.

Reich, Y., (1992). "Generation of Examples for Training a Learning Design System," *Proceedings of the ASCE Conference Computing in Civil Engineering*, Dallas.

Reich, Y. and Fenves, S., (1988). "Floor-System Design in SOAR: A Case Study of Learning to Learn," *Report*, Engineering Design Research Center, Carnegie Mellon University.

Reich, Y. and Fenves, S.J., (1992). "Automated Acquisition of Design Knowledge by Concept Formation," in *ASCE monograph Knowledge Acquisition in Civil Engineering*, T. Arciszewski and L. Rossman (Eds.).

Weiss, S.M. and Kulikowski, C.A., (1991). *Computers that Learn*, Morgan Kaufman Publishers, San Mateo, California.

Whitehall, B.L., Stepp, R.E. and Lu, S.C-Y, (1990). "Knowledge-Based Learning: Using Domain Theory to Guide Induction," *Annual Report of Knowledge-Based Engineering Systems Research Laboratory*, University of Illinois at Urbana-Champaign.

Wnek, J. and Michalski, R.S., (1991). "Hypothesis-driven Constructive Induction in AQ17: A Method and Experiments," *Proceedings of the IJCAI-91 Workshop on Evaluating and Changing Representations*, K. Morik, F. Bergadano and W. Buntine (Eds.), pp. 13-22, Sydney, Australia. (An extended version will appear in the Special Issue on Representation, *Machine Learning*.)

Wnek, J. and Michalski, R.S., (to appear). "Comparing Symbolic and Subsymbolic Learning: Three Studies," in *Machine Learning: A Multistrategy Approach*, Vol. IV, R.S. Michalski and G. Tecuci (Eds.), Morgan Kaufmann Publishers, San Mateo, CA.

Ziarko, W., (1989). "Data Analysis and Case-Based Expert System Development Tool ROUGH," *Proceedings of the Workshop on Case-Based Reasoning*, Pensacola Beach, Florida, Morgan Kaufman Publishers.